

Характеристики

Eaton 9E3000IR

Eaton 9E UPS, 3000 VA, 2700 W, Input: C20, Outputs: (6) C13, (1) C19, Rack, 2U

General specifications

PRODUCT NAME	Eaton 9E UPS
CATALOG NUMBER	9E3000IR
EAN	3553340710353
PRODUCT LENGTH/DEPTH	608 mm
PRODUCT HEIGHT	86.5 mm
PRODUCT WIDTH	438 mm
PRODUCT WEIGHT	31.3 kg
WARRANTY	2 year
COMPLIANCES	CE Marked TUV
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 CE

Додаткова інформація

AUTO SHUTDOWN FUNCTION	Yes
COLOR	Black
CONSTRUCTION TYPE	482.6 mm (19 inch) device
EFFICIENCY AT MAX. LOAD	91
HOT SWAP POWER	No
INTERNAL BYPASS	Yes

PACKAGE CONTENTS	• UPS • (2) IEC-IEC output cables • USB cable • Rack-mounting kit (rails and brackets) • Safety instructions • Quickstart guide
------------------	---

PHASE (INPUT)	1
PHASE (OUTPUT)	1
RACK MOUNTING KIT	Yes

Зв'язок

COMMUNICATION	• USB port (HID compliant) • Serial port (RS232) • Mini-terminal block for remote power off
---------------	---

ETHERNET INTERFACE	No
--------------------	----

EXPANSION SLOTS	One slot for optional communication card
-----------------	--

INCLUDES NETWORK CARD	No
-----------------------	----

POTENTIAL FREE SWITCH CONTACT	Yes
-------------------------------	-----

SOFTWARE COMPATIBILITY	Eaton Intelligent Power Manager, Eaton Intelligent Power Protector
------------------------	--

TYPE OF INTERFACE	Other
-------------------	-------

USER INTERFACE	Multilingual LCD display
----------------	--------------------------

Battery specifications

BATTERY MANAGEMENT	• Temperature compensated charging method • Automatic battery test • Deep discharge protection
--------------------	--

BATTERY QUANTITY	6
BATTERY RATING	12 V / 9 Ah
BATTERY REPLACEMENT	Replacable batteries
BATTERY TYPE	Sealed, lead-acid
EXTENDED BATTERY CAPABILITY	Yes
RUNTIME GRAPH	\$row.attributeValue.cdata

Електричні вхідні характеристики

INPUT CONNECTION	C14
INPUT CORD LENGTH	1.8m
INPUT FREQUENCY RANGE	40-70 Hz
INPUT NOMINAL VOLTAGE	230V default (220/230/240V)
INPUT POWER FACTOR	>.99
NOMINAL FREQUENCY	50/60 Hz

Електричні вихідні характеристики

FEED TYPE	1
OUTPUT NOMINAL VOLTAGE	230V default (220/230/240V)
OUTPUT POWER FACTOR	0.9
OUTPUT VOLTAGE RANGE	220/230/240 V +/- 2%
OUTPUT WAVEFORM	Sine wave
RECEPTACLE	(6) C13 + (1) C19
TOPOLOGY	Online/Double-conversion
VA RATING	3000 VA
VOLTAGE	230V
VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	3
WATTAGE	2700 W

Ресурси

DECLARATIONS OF CONFORMITY	EU Declaration of Conformity
ІНСТРУКЦІЇ ДЛЯ КОРИСТУВАЧА	9E Rack UPS quick start guide

Навколишнє середовище

ALTITUDE	3000 m
NOISE LEVEL	<45 dB at 1 meter
RELATIVE HUMIDITY	0-96% non-condensing
TEMPERATURE RANGE	0° to 40°C (32° to 104°F)

НАЗВА ПРОЕКТУ:

НОМЕР ПРОЕКТУ:

ПІДГОТУВАВ:

ДАТА:



Eaton Corporation plc Eaton House
30 Pembroke Road
Дублін 4, Ірландія
Eaton.com

© 2026 Eaton. Усі права захищені.

Стежте за нами в соціальних мережах, щоб отримувати актуальну інформацію про продукцію та технічну підтримку.

