

Характеристики

Фото репрезентативне

Eaton 9SX6KIRT3UG2

Eaton 9SX Gen2 UPS, 6000 VA, 6000 W,
Input: Hardwired, Outputs: (8) C13, (3) C19,
Hardwired, Rack/tower, 3U, Rack-mounting
kit included

General specifications

PRODUCT NAME	Eaton 9SX Gen2 UPS
CATALOG NUMBER	9SX6KIRT3UG2
EAN	3553340710667
PRODUCT LENGTH/DEPTH	684 mm
PRODUCT HEIGHT	130 mm
PRODUCT WIDTH	440 mm
PRODUCT WEIGHT	43.1 kg
WARRANTY	2 year
COMPLIANCES	LVD Directive (CB) EMC Directive RoHS Directive REACH WEEE Directive Packaging Directive Batteries Directive
CERTIFICATIONS	IEC/EN 62040-1 IEC/EN 62040-2 IEC/EN 62040-3 ENERGY STAR certified CE cULus UKCA Cm Ukr RCM KCC BSMI
MODEL CODE	Eaton 9SX 6000i RT3U G2

Додаткова інформація

AUTO SHUTDOWN FUNCTION

Yes

COLOR

Black

CONSTRUCTION TYPE

482.6 mm (19 inch) device

EFFICIENCY AT MAX. LOAD

96.5

HOT SWAP POWER

No

INTERNAL BYPASS

Yes

PACKAGE CONTENTS

- UPS
- (2) cable glands
- (2) IEC-IEC output cables (1,2m)
- USB cable (1,8m)
- Cable locking systems
- Supports for tower mounting
- Rack-mounting kit with brackets and slides for UPS
- Safety instructions
- Quickstart guide

RACK MOUNTING KIT

Yes

Battery specifications

BATTERY MANAGEMENT

- ABM+ (Predictive battery life) & Temperature compensated charging method (user selectable)
- Automatic battery test
- Deep discharge protection
- Automatic recognition of external battery units

BATTERY QUANTITY

15

BATTERY RATING

12 V / 5 Ah

BATTERY REPLACEMENT

Hot-swappable internal batteries and extended battery modules (EBMs)

BATTERY TYPE

Sealed, lead-acid

EXTENDED BATTERY CAPABILITY

Yes

RUNTIME GRAPH

\$row.attributeValue.cdata

Зв'язок

COMMUNICATION

- USB port (HID compliant)
- Serial port (RS232)
- Mini terminal block for remote On/Off
- Mini-terminal block for remote power off
- Mini-terminal block for dry contacts outputs (2 contacts)

ETHERNET INTERFACE	No
EXPANSION SLOTS	One slot
INCLUDES NETWORK CARD	No
POTENTIAL FREE SWITCH CONTACT	Yes
SOFTWARE COMPATIBILITY	Eaton Brighthouse Software suite
TYPE OF INTERFACE	Other
USER INTERFACE	Multilingual graphical LCD display

Електричні вихідні характеристики

FEED TYPE	1
OUTPUT NOMINAL VOLTAGE	230V default (200/208/220/230/240V)
OUTPUT POWER FACTOR	1
OUTPUT WAVEFORM	Sine wave
RECEPTACLE	(8) C13, (3) C19, Hardwired
TOPOLOGY	Online/Double-conversion
VA RATING	6000 VA
VOLTAGE	230V
VOLTAGE DISTORTION OUTPUT (LINEAR LOAD) - MAX	1
WATTAGE	6000W

Ресурси

Електричні вхідні характеристики

INPUT FREQUENCY RANGE	40-70 Hz
INPUT POWER FACTOR	>.99
INPUT VOLTAGE RANGE	176-276 V (100-276 V with derating)
NOMINAL FREQUENCY	50/60 Hz

НАЗВА ПРОЕКТУ:

НОМЕР ПРОЕКТУ:

ПІДГОТУВАВ:

ДАТА:



Eaton Corporation plc Eaton House
30 Pembroke Road
Дублін 4, Ірландія
Eaton.com

© 2026 Eaton. Усі права захищені.

Стежте за нами в соціальних мережах, щоб отримувати актуальну інформацію про продукцію та технічну підтримку.

