Стоечный источник бесперебойного питания 2000 Вольт-ампер

EG-UPSRACK-12



ПОЛНАЯ ЗАЩИТА.

- Обеспечивает бесперебойное питание предотвращает потерю данных
- Защищает ваше ценное оборудование.
- Защищает пользователей

Особенности

- Автоматичекий регулятор выходного напряжения (AVR)
- USB-интерфейс для управления и индикации
- ЖК-дисплей индикации статуса
- Защита от коротких замыканий
- Защита от выбросов напряжения, помех и молний
- Звуковое и визуальное оповещение о событиях
- Защита батареи от перезаряда и глубокого разряда

Спецификация

UPS type: line interactive, pure sine wave
Input: 220V AC ± 25%, 50Hz / 60Hz ± 10%
Output: 220V AC ± 10%, 50Hz / 60Hz ± 0.5% (on battery)
Output power factor: 0.8
Inverter output efficiency (resistive load): 85%, any load type is allowed

Switching time: no more than 10 ms (typically 6 ms)
Backup time: 8...20 mins (depends on the load)
Battery: 151 x 65 x 95 mm, sealed lead-acid 12 V / 9 Ah / 2.3 kg x 3 pcs

Charge time: up to 12 hours
Sockets: input IEC C14, outputs: Schuko EU type x 1 pc, IEC C13 x 6 pcs

Operating conditions: 0°C~40°C, at humidity 10~90%RH non condensing

Noise: < 45 dB (at 1 meter distance)
Power: 2000 VA (1600 W)
Dimensions: 440 x 410 x 132 mm
Product weight: 19.8 kg
"Cold-start" function

Упаковка

Кол-во в коробке, шт	1
Объем коробки, куб.м.	0.076632
Вес коробки, кг	25.06
Размеры индивидуальной упаковки ДхШхВ:	525x400x225 mm
Размеры картонной коробки ДхШхВ:	620x515x240 mm
Страна происхождения	CN
Баркод	8716309087735
Таможенный код	8504408590

Содержимое упаковки

UPS
Power cord
USB cable
Software CD
Spare fuse

Сертификаты

Системные требования

In order to work correclty, the connected load should be at least 5% of the maximum capacity of the UPS. For example, a 700 W UPS needs at least a connected load of 35 W to work.

Copyright © 2009–2025, Gembird Software Ltd.

Wittevrouwen 56 | 1358CD Almere | The Netherlands | Phone: +31-36-5211588
www.energenie.com | postmaster@energenie.com