

GENPOWE

Gasoline Generator

230V - 50Hz & 110V - 60Hz

GBG 110E & GBG 120E



Features and Benefits

- Half century experience in generator manufacturing
- Gasoline engines with advanced technology and quality
- Alternators with advanced technology and quality
- Easy to Carry
- High quality and reliable technology
- Compact Design and Silent
- Suitable for heavy-duty
- Durable
- Wide range of affordable spare parts

- Low noise level
- Low exhaust emission
- Low operating cost
- Low fuel consumption
- Low oil consumption
- Lightweight
- Big Size Fuel Tank
- First class product support
- Global technical service and maintenance support

Generator General Information														
Generator Model	Frequency Hz	Voltage V	Power Factor CosQ	Speed rpm	Gasoline Engine		Alternator			Type of Operation	Generator Output			
	112				Brand	Model	Series	Brand	Model	Series	Operation	kVA	kW	Α
GBG 110E	50	230	0.8	3000	GENPOWER 190						Maximum	10,5	8,4	45,7
						FB GFN	GENPOWER GNF	GNP	110L	Rated	9,0	7,2	39,1	
GBG 120E	60	60 110 3600	CLIV OVILI	130	FB	GLIV-UWLK	uiv		Maximum	12,0	9,6	109,1		
GBG 120E	00			3000						Rated	9,6	7,7	87,3	

Gasoline Engine General Data

- Single Cylinder, with Carburettor
- OHV (Over Head Valve) Technology
- 3000 rpm 50Hz / 3600 rpm 60Hz
- Air Cooled • Electronic Ignition - TCI System
- 4 Stroke
- Big Size and Silent Muffler
- Big Size Air Filter
- 12V Electric Start and Recoil Starting

Equipment and Features

- Heavy Duty Type Strong Base Frame
- Robotic Painting with Heavy Duty Electrostatic Powder Paint
- Durable Vibration Chocks Between Generator-Chassis
- Big Size Fuel Tank
- Fuel Level Gauge
- Fuel Tank Cap, with Ventilation
- Grounding Terminal
- Low Oil Level Alarm and Protection

Gasoline Engine Technical Data

Gasoline Engine reclinical Data					
Brand		Genpower			
Model		GBE 190FB			
Speed	rpm	3000 / 3600			
Displacement	cm ³	460			
Number of Cylinders		1			
Bore x Stroke	mm	92 x 69			

Dimensions		
Width *	Net (with Box)- mm	520 (525)
Length *	Net (with Box)- mm	682 (687)

Alternator

- Synchron Alternator
- Single Phase 230V / 110V
- Self Excited
- Power Factor: Cos Q: 0,8 / 1,0
- H or F Insulation Class
- IP 23 Protection Class
- Frequency: 50 Hz / 60 Hz
- %100 Copper Winding (Rotor and Stator)
- With AVR
- %10-15 Total Harmonic (THD)

Control Panel

- 2 pcs 16A Schuko witp Cap
- 1 pcs 12V DC Output
- 1 pcs Analoque Voltmeter
- 1 pcs Circuit Breaker
- 1 pcs Fuse
- 1 pcs Start Key
- 1 pcs Grounding Terminal

Cooling System		Air Cooled
Starting System		12V Electric Start and Recoil
Running Time- %50 loading	Hour	9
Fuel		Gasoline
Oil Capacity	It	1,1
Fuel Tank Capacity	lt	27

Height *	Net (with Box)- mm	555 (560)
Weight *	Net (with Box)- Kgr	91 (93)

^{*} Without handle and wheel

Important Note 1: Never use the generators in closed areas

Important Note 2: Wait 20 min for the generator to cool down before putting in fuel





Factory Address O II. Industrial Zone 2010 Street No: 18